





Product Featured: Argento Al Contro & Grigio Al Contro

## TREVI COLLECTION


Trevi Porcelain Collection from Country Floors features three beautiful cool color tones in a honed finish. Originating from Italy, the dramatic veining with infinite hues defines its modern beauty. Applicable for flooring or wall covering, this porcelain is sure to make a unique statement to any design.

### GRIGIO AL CONTRO

### FLOOR / WALL TILE




WIS11889 Grigio Al Contro Honed 12" x 24"



WIS11892 Bianco Al Contro Honed 6" x 24"



WIS11891 Bianco Al Contro Honed 24" x 48"



WIS11890 Bianco Al Contro Honed 8" x 48"

## BIANCO AL CONTROLLO

## FLOOR / WALL TILE

---



WIS11885 Bianco Al Controllo Honed 12" x 24"



WIS11888 Bianco Al Controllo Honed 6" x 24"



WIS11887 Bianco Al Controllo Honed 24" x 48"



WIS11886 Bianco Al Controllo Honed 8" x 48"

## ARGENTO AL CONTROLLO

## FLOOR / WALL TILE

---



WIS11893 Argento Al Controllo Honed 12" x 24"



WIS11896 Argento Al Controllo Honed 6" x 24"



WIS11895 Argento Al Controllo Honed 24" x 48"



WIS11894 Argento Al Controllo Honed 8" x 48"

# Trevi Porcelain



Product Featured: Argento Al Contro 24" x 48"

## TECHNICAL FEATURES

PHYSICAL PROPERTIES	TEST	INDUSTRY STANDARDS	RESULTS COLORED BODY
Water Absorption Size Calibrated (non rectified)	ASTM C373	0.5% Maximum	≤ 0.1%
Rectified	ASTM C499	• Range of Thickness (inch) 0.040	≤ 0.040
	ASTM C499	• Average Facial Dimension ± 0.50%	≤ ± 0.50%
	ASTM C485	• Warpage ± 75% on any edge	≤ ± 0.75%
	ASTM C485	• Warpage ± 50% on diagonal	≤ ± 0.50%
	ASTM C502	• Wedging ± 0.50%	≤ ± 0.50%
Bond Strength Deep Abrasion Hardness (Mohs scale) Frost Resistance (Freeze/Thaw)	ASTM C499	• Range of Thickness (inch) 0.040	≤ 0.040
	ASTM C499	• Average Facial Dimension ± 0.25%	≤ 0.25%
	ASTM C485	• Warpage ± 0.40% on any edge	≤ 0.40%
	ASTM C485	• Warpage ± 0.40% on diagonal	≤ 0.40%
	ASTM C502	• Wedging ± 0.25%	≤ 0.25%
Chemical Resistance Breaking Strength Coefficient of Friction (static)	ASTM C482	50 psi or greater	> 200 psi
	ASTM C1243	< 175 mm <sup>3</sup>	< 150 mm <sup>3</sup>
	ASTM C1026	No requirement No sample must show alterations to surface	≥ 7 No cracking or spalling occurred
	ASTM C650	No requirement	Class A
	ASTM C648	250 lbf or greater	≥ 350 lbf
	ASTM C1028	No requirement	Per collection

C1028 Acutest  
COF DCOF  
Dry ≥ 0.80 Wet ≥ 0.42  
Wet ≥ 0.60

## PACKING LIST

PRODUCT	SIZE	BOX PIECES	BOX SF	PALLET BOXES	PALLET SF	THICK- NESS	WEIGHT LB/SF
Floor & Wall Tile	24 x 48	4	31.668	15	587.58	8	3.55
	8 x 48	4	10.39	42	798.78	8	3.55
	12 x 24	8	15.751	32	504.032	8	3.55
	6 x 24	16	15.585	40	623.4	8	3.55
Bullnose	4 x 24	16	10.393	-	-	8	2.00

Data taken from a representative colored body collection. Individual product testing can be conducted by request.

Coefficient of Friction: All values given are for matte or honed material. No values are given for polished material. Country Floors does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

(All values are based on ASTM C1028 and Acutest DCOF.)

